

AC-215

Advanced Scalable Networked Access Controller



THE STATE-OF-THE-ART SINGLE/DUAL DOOR AC-215 NETWORKED ACCESS CONTROLLER IS THE BACKBONE OF MEDIUM SCALE SECURITY SYSTEMS HANDLING UP TO 5,000 USERS AND 2046 DOORS. DRIVEN BY ROSSLARE'S POWERFUL, FLEXIBLE, AND EASY TO USE AXTRAXNG™ SOFTWARE, THE SYSTEM PROVIDES AN IDEAL MODULAR AND EXPANDABLE SOLUTION FOR COMMERCIAL AND INSTITUTIONAL NEEDS. IT PROVIDES SEAMLESS INTEGRATION WITH ROSSLARE'S RANGE OF RFID PROXIMITY, PIN, PIN & PROX, SMARTCARD AND BIOMETRIC READERS WITH ROSSLARE'S SELECTION OF RFID CREDENTIALS.

GENERAL DESCRIPTION

AC-215 is suitable for applications with up to 5000 users across a modular 2046 doors, allowing maximum flexibility for securing a growing enterprise.

Each AC-215 access control unit (ACU) supports two readers (In/Out) of various formats including standard Wiegand 26-bit. Each ACU can be set to work as a single or double door controller.

The AC-215 is ready for installation with a mountable and lockable metal enclosure integrated with a transformer, power supply/charger, sounder and control board.

Using RS-232, RS-485, or PSTN communication means, multiple local or remote site networks can connect to the AxTraxNG™ Client/Server PC software running on Microsoft® Windows® XP / 7 operating systems.

MAIN FEATURES

- Up to 5000 users with access rights for every panel, across 2046 modular doors in a system
- 5000 'First In First Out' history event log, when offline
- Panel supports both 1-door (In/Out) and 2-door (In/Out, In/In or Out/Out) configurations
- Internal charger for external battery backup

- Supports PIN-only, PIN & PROX, or PROX-only readers
- Pre-installed enclosure components:
 - AC-AC power transformer, power supply/charger unit
 - Sounder unit
 - Space for a 7 AH SLA backup battery
 - Tamper switch
- Rugged, hinged metal enclosure that is lockable and vandal-resistant
- Real-time clock keeps time for up to 2 weeks without power. No batteries to replace
- 4-state supervised inputs (resistors included)

AxTraxNG™ CLIENT/SERVER SOFTWARE

- Based on SQL Express 2005 database
- Enables management of user data, photo with custom fields, access rights, alarms, strike times, and door modes from a central location
- Produces reports from acquired data, such as entry and exit times, and by alarm type with filters for user(s), location, and time
- Available in a large selection of languages

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ ACU Power Supply Voltage	12 VDC, regulated from PS-14 regulated power supply module
■ ACU Power Supply Max Current	500 mA input current limitation (PS-14)
■ ACU Input Current	Standby: 125 mA at 12 VDC, Maximum: 325 mA at 12 VDC
■ Relays	Four 5 A, N.O. and N.C. Form-C relays
■ Maximum Current for Readers	300 mA at 12 VDC

OPERATIONAL SPECIFICATIONS

■ Capacity	5000 users and 20,000 users without rights (Time & Attendance)
■ History Event Log Size	5000 events
■ Inputs	Four high-impedance, active low supervised inputs. Max. 5 VDC
■ Readers	Two Wiegand 26/32/34/37/40-Bit / C&D reader ports with tamper and LED control, 4-, 6- and 8-Bit burst keypad transmission support
■ Connectivity	RS-485/232, Dial-up (using MD-N33), TCP/IP (using MD-N32)
■ Networking	32 units/subnet on RS-485
■ Audio/Visual	Built-in sounder (Alarm, Chime, Bell) 8 on-board LEDs and 3 LEDs on power supply (PS-14)
■ Modes of Operation	Single Door (In/In), Dual Door (In/Out)
■ Time Zones and groups	32 multiple segment time zones, 64 holidays
■ Anti-Pass Back	Global anti-pass back (soft/hard), with 'forgive' option
■ Special Features	Interlock, first person delay, auto relock, scheduled outputs operation, 4 programmable site codes, extended unlocked time
■ Security Modes	Normal, Secure, Unlocked

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Indoor installation only
■ Operating Temperature	0°C to 49°C (32°F to 120°F)
■ Operating Humidity	0 to 85% (non-condensing)
■ RFI Protection	> 20 V/m up to 1000 MHz

PHYSICAL SPECIFICATIONS

■ ACU Board Dimensions	168 x 121 mm (6.61 x 4.76 in.)
■ Metal Enclosure	326 x 263 x 97 mm (12.8 x 10.4 x 3.82 in.)
■ Weight	2.4 kg (5.3 lbs) (including metal enclosure and transformer)

SYSTEM COMPONENTS

AC-215 is compatible with a range of Rosslare accessories, including a diverse selection of readers, accessories and serial converters to TCP/IP networks

PRODUCT WARRANTY

2-year Limited Product Warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

Visit our website: www.rosslaresecurity.com

Windows® is a registered trademark of Microsoft Corporation



ROSSLARE
SECURITY PRODUCTS
Experience The Difference