



SPEEDFACE 5SE Lite



Face



Live Body
Detection



QR
Code



Mifare



Wi-Fi



TCP/IP



Access
Control

Facial Attendance and Access Control

Storage Capacity

Face Capacity	10,000
Card Capacity	10,000
QR Capacity	10,000
Max User	10,000
Log Capacity	2,00,000

Features

5-inch capacitive touch screen.

DualCoreARM Cortex-A7 Processor.

Remotely Firmware Upgradation.

Live detection algorithm against color, Videos and 3D masks attack.

5-inch TN display all-sight LCD touch screen with 480*854 resolution.

Ip42 Grade Highly finished slim device.

Highly reliable and durable.

Recognition speed 0.5 seconds.



SpeedFace 5SE Lite

Communication Interface

Communication	Wi-Fi, TCP/IP, USB
---------------	--------------------

Biometric

Push Data	Yes
Remote firmware update	Yes
FAR	0.001%
Accuracy ratio	99.27%
Processor	Dual Core ARM Cortex-A7
OS	Linux
Verification time	<=1 second

Audio/Visual

LCD	5.0" TN touch screen display
Shutter type	Electronic Rolling Shutter
Language	English

Access control

Wiegand Out	Yes
Relay	Yes
Push button	Yes
Auxiliary	Input

Power & Environment

Operating Temperature	-10°C ~ 50°C
Power	12V DC / 2A
Dimension	186 x 94 x 23 mm



Auto Focus



Autofill light



Long Distance Verification

Software

Web & Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control